

FL 639 - Specifiche tecniche



Description

FL 639 è uno pneumatico Flotation per un impiego principalmente sul campo particolarmente idoneo per applicazioni con spargitori. L'impronta larga garantisce una ridotta compattazione del suolo che favorisce una maggiore produttività delle colture. Il battistrada rinforzato e la protezione del fianco contribuiscono ad un ciclo di vita più lungo. FL 639 assicura inoltre una trazione straordinaria nonché ottime proprietà di autopulitura.

UM

US Standard

Construction

RADIAL

Machinery

Agricoltura: Spargitore

Version	STANDARD
Type	TL
Tyre Size	800/40 R 22.5
LI/SS	168D/178A8

Dimensions US Standard

Usa code	94513420
Section Width (inch)	32.6
Overall Diameter (inch)	47.7
Static Loaded Radius (inch)	21.2
Rolling Circumference (inch)	143.4
Rim Rec	AG 28.00
ECE	E11-106R-0010830

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58
45	3600	4620	5740	6530	7540	8550	9340	10240	11240
40	3960	5070	6300	7160	8280	9390	10250	11240	12350
30	4780	6130	7630	8670	10020	11360	12410	13600	14950
25	5290	6780	8430	9590	11080	12570	13720	15050	16530
20	5970	7650	9510	10820	12500	14170	15490	16970	18650
15	6250	8000	9950	11320	13070	14840	16200	17760	19510
5	7120	9120	11340	12900	14890	16900	18450	20230	22220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/03/2025 11:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..