

## FLOTATION 558 - Specifiche tecniche



### Description

FLOTATION 558 è uno pneumatico Flotation a tele incrociate idoneo per mietitrici e presse per balle di fieno, autocisterne e rimorchi sia su strada che fuori strada. È particolarmente raccomandato in tutti i casi in cui la trazione è essenziale per una buona lavorazione del terreno oltre all'elevata capacità di carico.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	400/55 - 22.5
LI/SS DRIVE WHEEL	138 A8/134 B
LI/SS FREE ROLLING	150 A8/146 B

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	405
<b>Overall Diameter (mm)</b>	1020
<b>Static Loaded Radius (mm)</b>	445
<b>Rolling Circumference (mm)</b>	3084
<b>Rim Rec</b>	AG 11.75
<b>Rim Alt</b>	12.25 ; 13.00 ; AG 13.00
<b>ECE</b>	E4-106R-002261

## Load capacity (Kg)

km/h / bar	3.00	3.20	3.50
10 FR	4285	4450	4690
20 FR	3855	4005	4220
30 FR	3425	3560	3750
40 FR	3060	3180	3350
50 FR	2755	2860	3000
10 DW	3015	3135	3305
20 DW	2715	2820	2975
30 DW	2415	2510	2645
40 DW	2155	2240	2360
50 DW	1940	2015	2120

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..