

## FLOTATION 558 - Specifiche tecniche



### Description

FLOTATION 558 è uno pneumatico Flotation a tele incrociate idoneo per mietitrici e presse per balle di fieno, autocisterne e rimorchi sia su strada che fuori strada. È particolarmente raccomandato in tutti i casi in cui la trazione è essenziale per una buona lavorazione del terreno oltre all'elevata capacità di carico.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	500/45 - 22.5
LI/SS DRIVE WHEEL	136 A8/132 B
LI/SS FREE ROLLING	148 A8/144 B

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	500
Overall Diameter (mm)	1045
Static Loaded Radius (mm)	471
Rolling Circumference (mm)	3167
Rim Rec	AG 16.00
ECE	E4-106R-002307

## Load capacity (Kg)

km/h / bar	2.30	2.50	2.70
10 FR	4020	4215	4410
20 FR	3615	3795	3970
30 FR	3215	3370	3530
40 FR	2870	3010	3150
50 FR	2585	2710	2800
10 DW	2855	2995	3135
20 DW	2570	2695	2820
30 DW	2285	2395	2510
40 DW	2040	2140	2240
50 DW	1835	1925	2000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..