

FLOTATION 648 T - Scheda tecnica



Description

FLOTATION 648 T è particolarmente idoneo per la raccolta del fieno, nonché per il trasporto su campo e su strada. Lo speciale disegno del battistrada consente di trasportare carichi molto pesanti a pressioni basse garantendo delle eccezionali proprietà di autopulitura. Lo pneumatico è anche sinonimo di trazione e durabilità eccellenti.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Mietitrebbia

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
550/45 - 22.5	STANDARD	94029242	154 A8/150 B	166 A8/162 B	20	AG 16.00		21.7	42.1	18.7	126.1	TL	E4-106R-002046
550/45 - 22.5	STANDARD	94052066	147 A8/144 B	159 A8/156 B	16	AG 16.00		21.7	42.1	18.7	126.1	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..