

## FLOTATION TR 678 - Specifiche tecniche



### Description

FLOTATION TR 678 è stato particolarmente sviluppato per attrezzi agricoli e rimorchi sia su strada sia fuori strada. Consente il trasporto di carichi pesanti a basse pressioni, assicurando allo stesso tempo una ridotta compattazione del suolo. Questo pneumatico garantisce eccellente trazione e ottime proprietà di autopulitura.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	280/60 - 15.5
LI/SS	128 A8

## Dimensions US Standard

Usa code	94050154
Section Width (inch)	10.8
Overall Diameter (inch)	29.5
Static Loaded Radius (inch)	14.1
Rolling Circumference (inch)	88.6
Rim Rec	8.0
ECE	E11-106R-004262

## Load capacity (lbs)

mph / psi	68
25	3970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..