

## FORESTECH - Specifiche tecniche



### Description

FORESTECH è uno pneumatico BKT con cinture in acciaio, idoneo per le applicazioni forestali con macchine forwarder (autocaricanti). Lo pneumatico offre eccellente trazione anche in condizioni di servizio pesante. Il tallone robusto e l'area della spalla rinforzata assicurano elevata resistenza alle perforazioni e una vita più lunga dello pneumatico. Pertanto, potrete svolgere senza preoccupazioni le operazioni più esigenti e difficili nella foresta.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Macchina forwarder

Version	STEEL BELTED
Type	TL
Tyre Size	710/40 - 22.5
LI/SS	161 A8/ 165 A2

## Dimensions International Standard

Ply Rating	20
Section Width (mm)	710
Overall Diameter (mm)	1165
Static Loaded Radius (mm)	550
Rolling Circumference (mm)	3612
Rim Rec	AG 24.00
ECE	E11-106R-005273
TRA Code	LS2

## Load capacity (Kg)

km/h / bar	5.0
40	4625
30	5000
10	5150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 01:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..