

FORESTECH - Specifiche tecniche



Description

FORESTECH è uno pneumatico BKT con cinture in acciaio, idoneo per le applicazioni forestali con macchine forwarder (autocaricanti). Lo pneumatico offre eccellente trazione anche in condizioni di servizio pesante. Il tallone robusto e l'area della spalla rinforzata assicurano elevata resistenza alle perforazioni e una vita più lunga dello pneumatico. Pertanto, potrete svolgere senza preoccupazioni le operazioni più esigenti e difficili nella foresta.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Macchina forwarder

Version	STEEL BELTED
Type	TL
Tyre Size	750/55 - 26.5
LI/SS	177 A8/184 A2

Dimensions International Standard

Ply Rating	20
Section Width (mm)	755
Overall Diameter (mm)	1485
Static Loaded Radius (mm)	680
Rolling Circumference (mm)	4467
Rim Rec	AG 24.00
ECE	E11-106R-003347
TRA Code	LS2

Load capacity (Kg)

	km/h / bar	5.00
	40	7300
	30	7810
	10	9000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 01:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..