

GF 304 - Specifiche tecniche



Description

GF 304 è uno pneumatico idoneo per le applicazioni con golf cart. GF 304 vi assicura il massimo comfort e l'ottima protezione del terreno. GF 304 è anche disponibile in versione "aramid belted", con cinture in aramide, per fornire maggiore resistenza alla perforazione.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Golf kart

| | |
|-----------|---------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 18 X 8.50 - 8 |

Dimensions International Standard

| | |
|----------------------------|-------------------------------|
| Ply Rating | 4 |
| Section Width (mm) | 216 |
| Overall Diameter (mm) | 460 |
| Static Loaded Radius (mm) | 202 |
| Rolling Circumference (mm) | 1334 |
| Rim Rec | 7.00 I - 55 ; I - 70 ; I - 90 |
| ECE | E11-106R-003442 |

Load capacity (Kg)

| km/h / bar | 1.50 |
|------------|------|
| 15 | 375 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 23:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..