

## IT 400 - Specifiche tecniche



### Description

IT 400 è uno pneumatico con disegno del battistrada a blocchi per il principale impiego su strada nelle applicazioni di trasporto per rimorchi a pianale abbassato. Lo pneumatico è idoneo per applicazioni ad alta velocità e garantisce significativi risparmi di carburante.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Rimorchio a pianale abbassato

Version	STANDARD
Type	TT
Tyre Size	10.00 - 15
LI/SS	141/136 J

## Dimensions US Standard

Usa code	94008254
Ply Rating	16
Section Width (inch)	10.8
Overall Diameter (inch)	36.4
Static Loaded Radius (inch)	16.1
Rolling Circumference (inch)	108.1
Rim Rec	7.5
Rim Alt	7.0 ; 8.0
ECE	E11-54R-0018588

## Load capacity (lbs)

mph / psi	125	115	105
10	9085	-	-
20	-	7495	-
62 LS	-	5675	-
62 LD	-	-	4940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..