

## JUMBO TRAX HD - Specifiche tecniche



### Description

JUMBO TRAX HD è uno pneumatico con battistrada a blocchi per le pale skid steer. Lo pneumatico si distingue per la sua particolare resistenza ai tagli ed agli strappi ed è particolarmente idoneo per il servizio pesante. Il battistrada profondo insieme all'eccellente protezione dei fianchi garantisce un ciclo di vita esteso dello pneumatico. JUMBO TRAX HD è anche disponibile in versione "special".

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

## Dimensions US Standard

Usa code	94017294
Ply Rating	10
Section Width (inch)	12.8
Overall Diameter (inch)	33.7
Static Loaded Radius (inch)	15.2
Rolling Circumference (inch)	99.3
Rim Rec	9.75
ECE	E11-106R-005563

## Load capacity (lbs)

mph / psi	65
5	5600
10	4420
15	4090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..