

## LG 306 - Scheda tecnica



### Description

LG 306 è uno pneumatico per tappeti erbosi e il giardinaggio, idoneo per tosaerba. In alcune misure, LG 306 è anche adatto per piccoli trattori. Lo specifico disegno del battistrada, rende lo pneumatico delicato sul terreno, facilitando nel contempo la manipolazione e le manovre. LG 306 è disponibile in una versione "aramid-belted", con cinture in aramide, per utilizzatori che richiedono una maggiore resistenza alla perforazione.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Tosaerba • Trattorino

SIZE	Version	USACode	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
11 X 4.00 - 5	STANDARD	94027644			4	3.00 A		4.1	10.7	4.7	31.1	TL	E11-106R-004403
13 X 5.00 - 6	STANDARD	94030293			6	3.50 A		5	12.8	5.7	37.1	TL	E11-106R-004404
13 X 5.00 - 6	STANDARD	94012336			4	3.50 A		5	12.8	5.7	37.1	TL	E11-106R-003446
15 X 6.00 - 6	STANDARD	94012343			4	4.50 A		6	14.4	6.3	41.7	TL	E4-106R-002174
15 X 6.00 - 6	STANDARD	94030347			6	4.50 A		6	14.4	6.3	41.7	TL	E11-106R-004405
16 X 6.50 - 8	ARAMID BELTED	94012756			6	5.375   - 55 ;   - 70 ;   - 90		6.7	16.1	7.2	46.6	TL	E11-106R-003499
16 X 6.50 - 8	STANDARD	94041718			8	5.375   - 55 ;   - 70 ;   - 90		6.7	16.1	7.2	46.6	TL	E11-106R-004406
16 X 6.50 - 8	STANDARD	94012367			6	5.375   - 55 ;   - 70 ;   - 90		6.7	16.1	7.2	46.6	TL	E4-106R-002175
16 X 6.50 - 8	STANDARD	94012350			4	5.375   - 55 ;   - 70 ;   - 90		6.7	16.1	7.2	46.6	TL	E11-106R-003447
16 X 7.50 - 8	ARAMID BELTED	94062799			4	5.375   - 55 ;   - 70 ;   - 90		7	15.7	0	0	TL	E11-106R-006731
18 X 8.50 - 8	ARAMID BELTED	94012763			6	7.00   - 55 ;   - 70 ;   - 90		8.5	17.7	8	53	TL	E11-106R-003500
18 X 8.50 - 8	STANDARD	94012374			4	7.00   - 55 ;   - 70 ;   - 90		8.5	17.7	8	53	TL	E11-106R-003448
18 X 8.50 - 8	STANDARD	94012381			6	7.00   - 55 ;   - 70 ;   - 90		8.5	17.7	8	53	TL	E11-106R-003450
18 X 9.50 - 8	ARAMID BELTED	94012770			6	7.00   - 55 ;   - 70 ;   - 90		9.1	18.5	8.1	53.7	TL	E11-106R-003501
18 X 9.50 - 8	STANDARD	94012411			6	7.00   - 55 ;   - 70 ;   - 90		9.1	18.5	8.1	53.7	TL	E4-106R-002176
18 X 9.50 - 8	STANDARD	94012398			4	7.00   - 55 ;   - 70 ;   - 90		9.1	18.5	8.1	53.7	TL	E11-106R-003449
20 X 10.00 - 8	ARAMID BELTED	94012794			6	8.00   - 55	7.00   - 55 ;   - 70 ;   - 90	10	20	8.7	58	TL	E11-106R-003502
20 X 10.00 - 8	STANDARD	94012473			4	8.00   - 55	7.00   - 55 ;   - 70 ;   - 90	10	20	8.7	58	TL	E11-106R-003451
20 X 10.00 - 8	STANDARD	94012497			6	8.00   - 55	7.00   - 55 ;   - 70 ;   - 90	10	20	8.7	58	TL	E11-106R-003379
18 X 8.50 - 10	STANDARD	94027637			4	7.00   - 55 ;   - 70 ;   - 90		8.3	18.1	8.1	53.9	TL	E11-106R-003452
20 X 10.00 - 10	ARAMID BELTED	94012787			6	8.00   - 55	7.00   - 55	9.8	20	8.9	58	TL	E11-106R-003503
20 X 10.00 - 10	STANDARD	94012459			6	8.00   - 55	7.00   - 55	9.8	20	8.9	58	TL	E11-106R-003455
20 X 10.00	STANDARD	94012435			4	8.00   - 55	7.00   - 55	9.8	20	8.9	58	TL	E11-

- 10											106R-003453		
20 X 8.00 - 10	STANDARD	94012725			4	6.00   - 55 ;   - 70 ;   - 90	6 JA	8.1	19.7	8.8	57.1	TL	E11-106R-003454
20 X 8.00 - 10	STANDARD	94012732			6	6.00   - 55 ;   - 70 ;   - 90	6 JA	8.1	19.7	8.8	57.1	TL	E11-106R-003456
23 X 10.50 - 12	ARAMID BELTED	94012800			6	8.5   - 55	7.00   - 55 ;   - 70 ;   - 90	10.2	23	10.3	66.8	TL	E11-106R-003580
23 X 10.50 - 12	STANDARD	94012534			6	8.5   - 55	7.00   - 55 ;   - 70 ;   - 90	10.2	23	10.3	66.8	TL	E4-106R-002177
23 X 10.50 - 12	STANDARD	94012510			4	8.5   - 55	7.00   - 55 ;   - 70 ;   - 90	10.2	23	10.3	66.8	TL	E11-106R-003352
23 X 10.50 - 12	STANDARD	94012558			8	8.5   - 55	7.00   - 55 ;   - 70 ;   - 90	10.2	23	10.3	66.8	TL	E4-106R-002661
23 X 10.50 - 12	STANDARD	94012572			12	8.5   - 55	7.00   - 55 ;   - 70 ;   - 90	10.2	23	10.3	66.8	TL	E4-106R-002665
23 X 8.50 - 12	ARAMID BELTED	94028252			6	7.00   - 55 ;   - 70 ;   - 90	7 JA	8.3	22.6	10.2	67.3	TL	E11-106R-004409
23 X 8.50 - 12	STANDARD	94012640			12	7.00   - 55 ;   - 70 ;   - 90	7 JA	8.3	22.6	10.3	67.6	TL	E4-106R-002835
23 X 8.50 - 12	STANDARD	94012589			4	7.00   - 55 ;   - 70 ;   - 90	7 JA	8.3	22.6	10.2	67.3	TL	E11-106R-003457
23 X 8.50 - 12	STANDARD	94012602			6	7.00   - 55 ;   - 70 ;   - 90	7 JA	8.3	22.6	10.2	67.3	TL	E4-106R-002178
23 X 8.50 - 12	STANDARD	94012626			8	7.00   - 55 ;   - 70 ;   - 90	7 JA	8.3	22.6	10.2	67.3	TL	E11-106R-003458
24 X 12.00 - 12	STANDARD	94042074			4	9.5 AT	9.0 AT ; 8.5 AT ; 8.0 AT	11.7	24	10.9	69.8	TL	E11-106R-004407
26 X 12.00 - 12	ARAMID BELTED	94012817			6	10.50   - 55 ;   - 70 ;   - 90	10½ JA ; 8½ JA	12.2	25.2	11.1	73.1	TL	E11-106R-003384
26 X 12.00 - 12	ARAMID BELTED	94012824			8	10.50   - 55 ;   - 70 ;   - 90	10½ JA ; 8½ JA	12.2	25.2	11.1	73.1	TL	E11-106R-005304
26 X 12.00 - 12	STANDARD	94012671			8	10.50   - 55 ;   - 70 ;   - 90	10½ JA ; 8½ JA	12.2	25.2	11.1	73.1	TL	E4-106R-002674
26 X 12.00 - 12	STANDARD	94012718			14	10.50   - 55 ;   - 70 ;   - 90	10½ JA ; 8½ JA	12.2	25.2	11.6	76.6	TL	E4-106R-002327
26 X 12.00 - 12	STANDARD	94012657			4	10.50   - 55 ;   - 70 ;   - 90	10½ JA ; 8½ JA	12.2	25.2	11.1	73.1	TL	E11-106R-003459
26 X 12.00 - 12	STANDARD	94012695			12	10.50   - 55 ;   - 70 ;   - 90	10½ JA ; 8½ JA	12.2	25.2	11.1	73.1	TL	E11-106R-003524
260/55 - 12 (23 X 10.50 - 12)	IMPLEMENT	94067978	110 A8	122 A8	14	8.5   - 55	7.00   - 55 ;   - 70 ;   - 90	10.2	23	10.3	66.8	TL	E11-106R-006955
24 X 8.50 - 14	STANDARD	94042111			4	7 JA		8.3	24	11	69.6	TL	E11-106R-004582
25 X 8.50 - 14	STANDARD	94036622			6	7.00   - 55 ;   - 70 ;   - 90		8.7	25.1	11.6	75.4	TL	E11-106R-003460
25 X 8.50 - 14	STANDARD	94065547			8	7.00   - 55 ;   - 70 ;   - 90		8.7	25.1	11.6	75.4	TL	E11-106R-006732

<b>27 X 10.50 - 15</b>	STANDARD	94029822	4	8.00 LB		10.7	27.8	12.5	80.4	TL	E11-106R-006848
<b>27 X 10.50 - 15</b>	STANDARD	94031702	12	8.00 LB		10.7	27.8	12.5	80.4	TL	E11-106R-006849
<b>27 X 8.50 - 15</b>	STANDARD	94025671	4	7.00 JA		8.5	27	13	81.7	TL	E4-106R-002204
<b>29 X 12.50 - 15</b>	ARAMID BELTED	94062782	10	10 LB		12.5	29.1	13.7	87.8	TL	E11-106R-006167
<b>31 X 15.5 - 15</b>	ARAMID BELTED	94062775	8	13 LB		15.4	31.2	13.8	91.1	TL	E11-106R-006735
<b>31 X 15.5 - 15</b>	STANDARD	94042104	4	13 LB		15.4	31.2	13.8	91.1	TL	E11-106R-004083
<b>31 X 15.5 - 15</b>	STANDARD	94058600	8	13 LB		15.4	31.2	13.8	91.1	TL	E11-106R-007115
<b>13.6 - 16</b>	STANDARD	94036646	4	W 12	W 11	15.3	38.4	17.4	112.6	TL	E4-106R-002206
<b>33 X 15.50 - 16.5</b>	STANDARD	94037100	10	12.00		15.6	33.1	15.2	99.9	TL	E11-106R-003004
<b>38 X 14.00 - 20</b>	STANDARD	94012749	4	W 11	W 11 H	14.8	38.6	17.6	114.6	TL	E4-106R-002210
<b>44 X 18.00 - 20</b>	STANDARD	94030231	4	W 14 L	W 14 LH	19.3	45.9	20.4	138.1	TL	E11-106R-006828

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 22:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..