

LOADER PLUS - Specifiche tecniche



Description

LOADER PLUS (L-3) è uno pneumatico a struttura diagonale, particolarmente progettato per loader. La mescola del battistrada offre delle caratteristiche di resistenza ad ogni tipo di taglio ed è ideale per operazioni di carico o livellamento.

UM

International Standard

Construction

BIAS

Machinery

Industriale: Dozer • Pala caricatrice

OTR: Dozer • Pala caricatrice

Version	STANDARD
Type	TL
Tyre Size	26.5 - 25

Dimensions International Standard

Ply Rating	28
Overall Width (mm)	680
Overall Diameter (mm)	1740
Static Loaded Radius (mm)	796
Rolling Circumference (mm)	5150
Rim Rec	22.00/3.0
TRA Code	L3

Load capacity (Kg)

km/h / bar	4.75
10	15500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 00:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..