

## LOADER PLUS - Scheda tecnica



### Description

LOADER PLUS (L-3) è uno pneumatico a struttura diagonale, particolarmente progettato per loader. La mescola del battistrada offre delle caratteristiche di resistenza ad ogni tipo di taglio ed è ideale per operazioni di carico o livellamento.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Dozer • Pala caricatrice

OTR: Dozer • Pala caricatrice

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 25	STANDARD	L3	20	10.00/1.5		375	1368	630	4050	TT
17.5 - 25	DUAL BEAD	L3	20	14.00/1.5		440	1345	622	3980	TT
17.5 - 25	STANDARD	L3	16	14.00/1.5		440	1345	622	3980	TT
17.5 - 25	STANDARD	L3	16	14.00/1.5		440	1345	622	3980	TL
20.5 - 25	STANDARD	L3	20	17.00/2.0		540	1490	685	4410	TT
20.5 - 25	STANDARD	L3	20	17.00/2.0		540	1490	685	4410	TL
20.5 - 25	STANDARD	L3	16	17.00/2.0		540	1490	685	4410	TT
20.5 - 25	STANDARD	L3	16	17.00/2.0		540	1490	685	4410	TL
23.5 - 25	STANDARD	L3	24	19.50/2.5		610	1640	749	4855	TL
23.5 - 25	STANDARD	L3	16	19.50/2.5		610	1640	749	4855	TT
23.5 - 25	STANDARD	L3	16	19.50/2.5		610	1640	749	4855	TL
23.5 - 25	STANDARD	L3	20	19.50/2.5		610	1640	749	4855	TT
23.5 - 25	STANDARD	L3	20	19.50/2.5		610	1640	749	4855	TL
26.5 - 25	STANDARD	L3	32	22.00/3.0		680	1740	796	5150	TL
26.5 - 25	STANDARD	L3	28	22.00/3.0		680	1740	796	5150	TL
29.5 - 25	STANDARD	L3	28	25.00/3.5		760	1860	849	5544	TL
29.5 - 25	STANDARD	L3	32	25.00/3.5		760	1860	849	5544	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 00:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..