

## LUG STAR - Specifiche tecniche



### Description

LUG STAR è un pneumatico industriale particolarmente sviluppato per applicazioni con escavatori su rotaie/strada che richiedono trazione eccezionale. Si distingue per le eccellenti proprietà di autopulitura e una miscela molto resistente del battistrada. La carcassa robusta garantisce straordinaria durabilità.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Veicolo strada-rotaia

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

## Dimensions International Standard

Ply Rating	18
Overall Width (mm)	280
Overall Diameter (mm)	1080
Static Loaded Radius (mm)	506
Rolling Circumference (mm)	3343
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

## Load capacity (Kg)

km/h / bar	10.00
10	6890
25	5300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 20:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..