

## MAGLIFT - Specifiche tecniche



### Description

MAGLIFT è stato particolarmente progettato per tutte le operazioni con carrelli elevatori nei settori industriali e nella logistica. Questo pneumatico pieno si distingue per l'elevata capacità di carico nonché per l'eccezionale confort. MAGLIFT offre una straordinaria resistenza alla perforazione che si traduce in una lunga vita dello pneumatico. La struttura rinforzata riduce il rischio di slittamento, mentre la particolare forma del tallone facilita il montaggio sul cerchio.

### UM

US Standard

### Construction

◆ SOLID

### Machinery

Industriale: Carrello elevatore

Version

LIP - NON MARKING

Type

Tyre Size

4.00 - 8

## Dimensions US Standard

Usa code	94054633
TMPH	1
Section Width (inch)	4.3
Overall Diameter (inch)	16
Rim Rec	3.00 D - 8

## Load capacity (lbs)

mph / psi	-
15 LOAD WHEEL	2095
15 STEER WHEEL	1610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 06:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..