

## MINEFORCE - Specifiche tecniche



### Description

Il MINEFORCE è uno pneumatico a tele diagonali appositamente progettato per i camion da trasporto in attività estrattive all'interno di cave e miniere. Lo pneumatico per autocarri da trasporto ad alte prestazioni MINEFORCE è l'innovativa risposta di BKT alle esigenze poste da ambienti minerari rocciosi, abrasivi e difficili. Presenta un design di battistrada unico con mescole appositamente sviluppate per operazioni di scavo su terreni duri, rocciosi e complessi. L'ampia area di contatto dotata di alette rigide assicura un'usura uniforme del battistrada e un ciclo di vita più lungo.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Dumper rigido

Version	STANDARD
Type	TL
Tyre Size	27.00 - 49

## Dimensions International Standard

Ply Rating	54
TKPH	475
Overall Width (mm)	740
Overall Diameter (mm)	2695
Static Loaded Radius (mm)	1253
Rolling Circumference (mm)	7985
Rim Rec	19.50/4.0
TRA Code	E4

## Load capacity (Kg)

km/h / bar	6.50	8.75
50	27250	-
10	-	46970

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 16:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..