

MINEFORCE - Scheda tecnica



Description

Il MINEFORCE è uno pneumatico a tele diagonali appositamente progettato per i camion da trasporto in attività estrattive all'interno di cave e miniere. Lo pneumatico per autocarri da trasporto ad alte prestazioni MINEFORCE è l'innovativa risposta di BKT alle esigenze poste da ambienti minerari rocciosi, abrasivi e difficili. Presenta un design di battistrada unico con mescole appositamente sviluppate per operazioni di scavo su terreni duri, rocciosi e complessi. L'ampia area di contatto dotata di alette rigide assicura un'usura uniforme del battistrada e un ciclo di vita più lungo.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Dumper rigido

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
24.00 - 35	CUT RESISTANT	E4	48	17.00/3.5		655	2190	1003	6482	TL	370
27.00 - 49	STANDARD	E4	48	19.50/4.0		740	2695	1253	7985	TL	475
27.00 - 49	STANDARD	E4	54	19.50/4.0		740	2695	1253	7985	TL	475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 16:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..