

MP 567 - Specifiche tecniche



Description

MP 567 è uno pneumatico agro-industriale idoneo per il trasporto sia su campo che su strada, per operazioni nell'ambito municipalità/manutenzione. È lo pneumatico perfetto per sollevatori telescopici e attrezzi agricoli. Lo pneumatico MP 567 offre ottima trazione in tutte le condizioni atmosferiche, nonché delle eccellenti proprietà di autopulitura. Questo pneumatico garantisce un'esperienza di guida confortevole nonché una vita operativa prolungata.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Sollevatore telescopico
Industriale: Sollevatore telescopico • Veicolo universale

Version	IMPLEMENT
Type	TL
Tyre Size	11.5/80 - 15
LI/SS DRIVE WHEEL	123 A8
LI/SS FREE ROLLING	135 A8

Dimensions US Standard

Usa code	94054930
Ply Rating	12
Section Width (inch)	11.4
Overall Diameter (inch)	34.4
Rim Rec	8 LB
ECE	E11-106R-004621

Load capacity (lbs)

mph / psi	60
25 FR	4800
25 DW	3420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 06:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..