

## MP 600 - Specifiche tecniche



### Description

MP 600 è uno pneumatico agro-industriale idoneo per operazioni di municipalità/manutenzione con sollevatori telescopici e attrezzi agricoli, offrendo un'esperienza di guida confortevole. Lo pneumatico assicura ottima trazione ed eccellenti proprietà di autopulitura nonché un ciclo di vita prolungato del prodotto.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli • Sollevatore telescopico  
Industriale: Sollevatore telescopico • Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	400/70 - 20 (16.0/70 - 20)

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	405
<b>Overall Diameter (mm)</b>	1085
<b>Rim Rec</b>	13 SDC
<b>Rim Alt</b>	12

## Load capacity (Kg)

	km/h / bar	<b>4.00</b>
	40 DW	3550
	50 DW	3250

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..