

MUD POWER HD - Specifiche tecniche



Description

MUD POWER HD è stato specificamente progettato per pale skid steer. Il disegno profondo del battistrada, oltre alla disposizione speciale dei ramponi, assicura trazione eccellente su terreno bagnato e soffice. MUD POWER HD è stato realizzato con una miscela industriale speciale ed è caratterizzato da una carcassa robusta in nylon che assicurano un ciclo di vita più lungo dello pneumatico anche in condizioni severe.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Pala Skid Steer

Version	STANDARD
Type	TL
Tyre Size	12 - 16.5

Dimensions International Standard

Ply Rating	10
Section Width (mm)	315
Overall Diameter (mm)	850
Static Loaded Radius (mm)	391
Rolling Circumference (mm)	2514
Rim Rec	9.75
ECE	E11-106R-005563
TRA Code	R4

Load capacity (Kg)

	km/h / bar	4.50
	10	2540
	15	2005
	25	1855

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:20

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..