

MULTIMAX MP 519 - Specifiche tecniche



Description

MULTIMAX MP 519 è uno pneumatico particolarmente idoneo per autocarri leggeri in tutte le applicazioni di trasporto. La carcassa rinforzata con cinture in acciaio garantisce eccellente stabilità a velocità elevate (90 km/h). Grazie alla bassa resistenza di rotolamento, lo pneumatico assicura una riduzione nei consumi di carburante.

UM

International Standard

Construction

 RADIAL

Machinery

Industriale: Autocarro leggero

Version	STANDARD
Type	TL
Tyre Size	7.50 R 16 LT
LI/SS	109/107 G

Dimensions International Standard

Ply Rating	6
Section Width (mm)	220
Overall Diameter (mm)	810
Static Loaded Radius (mm)	377
Rolling Circumference (mm)	2449
Rim Rec	6.00
Rim Alt	5.50 F ; 6 L ; 7 L

Load capacity (Kg)

	km/h / bar	3.5
	90 LS	1030
	90 LD	975

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/09/2024 02:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..