

MULTIMAX MP 519 - Scheda tecnica



Description

MULTIMAX MP 519 è uno pneumatico particolarmente idoneo per autocarri leggeri in tutte le applicazioni di trasporto. La carcassa rinforzata con cinture in acciaio garantisce eccellente stabilità a velocità elevate (90 km/h). Grazie alla bassa resistenza di rotolamento, lo pneumatico assicura una riduzione nei consumi di carburante.

UM

US Standard

Construction

 RADIAL

Machinery

Industriale: Autocarro leggero

SIZE	Version	USACode	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
7.50 R 16 LT	STANDARD	94053384	109/107 G	6	6.00	5.50 F ; 6 L ; 7 L	8.7	31.9	14.8	96.4	TL	
7.50 R 16 LT	STANDARD	94063437	112/110G	8	6.00	5.50 F ; 6 L ; 7 L	8.7	31.9	14.8	96.4	TL	E11-54R-0019046

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28/09/2024 02:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..