

MULTIMAX MP 525 - Specifiche tecniche



Description

MULTIMAX MP 525 è uno pneumatico radiale All Steel polivalente, progettato per veicoli universali, sollevatori telescopici, pale compatte e motolivellatrici in applicazioni agroindustriali. Infatti, l'ampio disegno non direzionale del battistrada offre una trazione eccellente su qualsiasi superficie, oltre a eccezionali proprietà autopulenti. Il robusto fianco assicura straordinaria stabilità laterale in modalità di sollevamento, rendendolo la scelta ideale per le operazioni agricole e per la movimentazione dei materiali. MULTIMAX MP 525 è realizzato con una miscela del battistrada particolarmente resistente a tagli e strappi che si traduce in una maggiore vita operativa dello pneumatico grazie alla sua straordinaria resistenza a qualsiasi tipo di taglio e foratura.

UM

International Standard

Construction

RADIAL

Machinery

Agricoltura: Sollevatore telescopico • Veicolo universale
Industriale: Pala compatta • Motolivellatrice • Sollevatore telescopico

Version	STANDARD
Type	TL
Tyre Size	405/70 R 18 (15.5/70 R 18)
LI/SS	146 J/141 B/153 A2

Dimensions International Standard

Overall Width (mm)	405
Overall Diameter (mm)	1025
Static Loaded Radius (mm)	462
Rolling Circumference (mm)	3122
Rim Rec	13
Rim Alt	11; 12
ECE	E11-54R-0022030

Load capacity (Kg)

km/h / bar	3.75	4.00
100	2800	3000
50	2575	-
10	3650	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 03/02/2025 09:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..