

MULTIMAX MP 527 - Specifiche tecniche



Description

MULTIMAX MP 527 è uno pneumatico radiale polivalente sviluppato per sollevatori telescopici e pale compatte nelle applicazioni agro-industriali. Lo pneumatico è dotato di un disegno a blocchi del battistrada che garantisce eccellente trazione anche sulle superfici più dure. Il fianco robusto dello pneumatico assicura straordinaria stabilità in modalità di sollevamento. MULTIMAX MP 527 è realizzato con una mescola particolarmente resistente a tagli e lacerazioni che si traduce in una lunga vita operativa dello pneumatico.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Pala compatta • Sollevatore telescopico
Industriale: Pala compatta • Sollevatore telescopico

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 400/80 R 24 IND |
| LI/SS | 162 A8/B |

Dimensions US Standard

| | |
|------------------------------|---------------------------|
| Usa code | 94052226 |
| Section Width (inch) | 15.9 |
| Overall Diameter (inch) | 49.2 |
| Static Loaded Radius (inch) | 22.8 |
| Rolling Circumference (inch) | 150.9 |
| Rim Rec | DW 13 |
| Rim Alt | DW 12 ; DW 13 L ; DW 14 L |
| ECE | E11-106R-002982 |

Load capacity (lbs)

| mph / psi | 23 | 29 | 35 | 41 | 46 | 49 | 52 | 58 | 64 | 67 | 70 | 73 | 75 | 78 |
|-----------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 30 | 4090 | 4820 | 5650 | 6390 | 7120 | 7390 | 7760 | 8590 | 9300 | 9780 | 10010 | 10470 | - | - |
| 25 | 4090 | 4820 | 5650 | 6390 | 7120 | 7390 | 7760 | 8590 | 9300 | 9780 | 10010 | 10470 | - | - |
| 20 | 4380 | 5160 | 6060 | 6840 | 7630 | 7910 | 8310 | 9190 | 9950 | 10460 | 10710 | 11210 | - | - |
| 15 | 4540 | 5360 | 6280 | 7100 | 7910 | 8210 | 8620 | 9550 | 10340 | 10860 | 11110 | 11630 | - | - |
| 5 Cvc. | 5030 | 6140 | 7230 | 8490 | 9590 | 10140 | 10680 | 11640 | 12890 | 13430 | 13950 | 14670 | 15010 | 15710 |
| Static | 7720 | 9410 | 11090 | 13010 | 14700 | 15540 | 16380 | 17860 | 19750 | 20590 | 21410 | 22500 | 23030 | 24080 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..