

MULTIMAX MP 529 - Scheda tecnica



Description

MULTIMAX MP 529 è un pneumatico radiale multiuso con cinture in acciaio sviluppato per sollevatori telescopici nelle applicazioni industriali. Il disegno del battistrada è stato sviluppato appositamente per superfici dure. Il fianco robusto dello pneumatico e un'impronta a terra più larga assicurano straordinaria stabilità in modalità di sollevamento. MULTIMAX MP 529 si distingue inoltre per la carcassa robusta resistente alla foratura ed è realizzato con una mescola particolarmente resistente ai tagli e strappi che si traducono in durabilità elevata e in una lunga vita operativa dello pneumatico.

UM

US Standard

Construction

 RADIAL

Machinery

Industriale: Sollevatore telescopico

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
340/80 R 18	STANDARD	94054305	143 A8/B	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	13.5	39.4	17.5	118.4	TL	E11-106R-002972

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..