

MULTIMAX MP 540 - Specifiche tecniche



Description

MULTIMAX MP 540 è stato progettato da BKT per tutti i veicoli polivalenti. Grazie alla carcassa All Steel, MULTIMAX MP 540 consente di trasportare carichi pesanti durante l'uso su strada e fuori strada. Inoltre, il disegno a blocchi del battistrada offre stabilità e durata eccezionali.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Veicolo universale

Industriale: Veicolo universale

Version	STANDARD
Type	TL
Tyre Size	335/80 R 18 (12.5 R 18)
LI/SS	132 K

Dimensions International Standard

Overall Width (mm)	340
Overall Diameter (mm)	985
Static Loaded Radius (mm)	446
Rolling Circumference (mm)	3000
Rim Rec	11
ECE	E11-54R-0019559

Load capacity (Kg)

km/h / bar	3.50
110	2000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..