

## MULTIMAX MT 518 - Scheda tecnica



### Description

MULTIMAX MT 518 è stato specificamente sviluppato per autocarri militari. È uno pneumatico con disegno del battistrada a blocchi e cinture d'acciaio che si distingue per l'elevata resistenza alla perforazione nonché per la straordinaria stabilità. Inoltre, MULTIMAX MT 518 sostiene l'alta velocità ed assicura un ciclo di vita prolungato dello pneumatico.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industriale: Autocarro militare

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
36 X 12.5 R 16.5	STANDARD	94039517	129 N	9.75		12.4	35.5	16.5	108.6	TL	E11-54R-0017917

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 12:27

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..