

## MULTIMAX SR 261 - Specifiche tecniche



### Description

MULTIMAX SR 261 è uno pneumatico radiale interamente in acciaio con cinghie in acciaio multistrato appositamente progettato per rimorchi a piattaforma bassa, rimorchi agricoli e gru portuali mobili in applicazioni di trasporto e operazioni portuali.

La sua robusta carcassa e la speciale miscela del battistrada assicurano una maggiore durata dello pneumatico. Grazie al design a lamelle del battistrada, MULTIMAX SR 261 permette di usufruire di una trazione superiore in tutte le applicazioni.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industriale: Rimorchio a pianale abbassato • Gru mobile

Version	STANDARD
Type	TL
Tyre Size	215/75 R 17.5
LI/SS	135/133 J

## Dimensions US Standard

Usa code	94071067
Overall Width (inch)	8.3
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	93.3
Rim Rec	6.00
Rim Alt	6.75

## Load capacity (lbs)

	mph / psi	125
	62 Load Single	4805
	62 Load Dual	4540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 16:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..