

## PAC MASTER PLUS - Specifiche tecniche



### Description

PAC MASTER PLUS è un pneumatico diagonale per compattatori caratterizzato da un'area di contatto più larga offrendo maggiore stabilità. E' realizzato con una miscela speciale che fornisce elevata resistenza al calore. PAC MASTER PLUS assicura un ciclo di vita prolungato dello pneumatico.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Compattatore

Version	STANDARD
Type	TT
Tyre Size	7.50 - 15

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	225
Overall Diameter (mm)	790
Static Loaded Radius (mm)	375
Rolling Circumference (mm)	2385
Rim Rec	6.0
Rim Alt	6.5
ECE	E11-106R-005322

## Load capacity (Kg)

km/h / bar	8.75
10	2900
15	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 15:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..