

PAC MASTER - Specifiche tecniche



Description

PAC MASTERè uno pneumatico diagonale per compattatori. Fornisce elevata stabilità e assicura un ciclo di vita prolungato. Lo pneumatico è realizzato con una mescola speciale che fornisce particolare resistenza al calore.

UM

US Standard

Construction



Machinery

Industriale: Compattatore

Version	STANDARD
Туре	ΤΤ
Tyre Size	9.5/65 - 15

Dimensions US Standard

Usa code	94036141
Ply Rating	6
Section Width (inch)	9.3
Overall Diameter (inch)	26.6
Rim Rec	7.0
ECE	E11-106R-005303

Load capacity (lbs)

mph / psi	47
5	2910
10	2340

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 13:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..