

## PORTMAX PM 93 PLUS - Specifiche tecniche



### Description

PORTMAX PM 93 PLUS è stato particolarmente progettato per straddle carrier (gru a cavaliere) nelle operazioni portuali di movimentazione dei container. Lo pneumatico radiale All Steel con cinture in acciaio multistrato garantisce maggiore stabilità e durabilità. La speciale miscela antistatica del battistrada assicura eccellente resistenza al calore nonché una vita più lunga dello pneumatico. PORTMAX PM 93 PLUS offre una resistenza ridotta al rotolamento che migliora il risparmio di carburante.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Industriale: Straddle carrier

Version	INDUSTRIAL
Type	TL
Tyre Size	480/95 R25
LI/SS	208 A5

## Dimensions International Standard

Overall Width (mm)	470
Overall Diameter (mm)	1555
Static Loaded Radius (mm)	704
Rolling Circumference (mm)	4718
Rim Rec	13.00/2.5
Star Rating	***

## Load capacity (Kg)

km/h / bar	10
25	18000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/02/2025 18:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..