

POWER TRAX HD (FL) - Specifiche tecniche



Description

POWER TRAX HD è uno pneumatico a tele diagonali di alta qualità, appositamente progettato per carrelli elevatori in applicazioni industriali. Il battistrada profondo, la parete laterale extra spessa e il rivestimento resistente offrono una durata eccezionale riducendo al minimo il rischio di forature e danni accidentali. Lo pneumatico presenta un'eccellente resistenza al taglio, al truciolo e allo strappo per superfici in cemento ruvide e dure. La protezione dei cerchioni, appositamente progettata, previene danni alla piana e alle ruote nell'area della flangia del cerchione.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Carrello elevatore

Version	STANDARD
Type	TT
Tyre Size	250 - 15 (250/70 - 15)

Dimensions US Standard

Usa code	94007745
Ply Rating	20
Section Width (inch)	9.4
Overall Diameter (inch)	29.3
Rim Rec	7.50
Rim Alt	7.0

Load capacity (lbs)

mph / psi	145
15 LOAD WHEEL	11110
15 STEER WHEEL	8540
5 OTHER VEHICLES	11110
15 OTHER VEHICLES	8540
STATIC SIDE LOADER	12895

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..