

## POWER TRAX HD SMOOTH - Scheda tecnica



### Description

POWER TRAX HD SMOOTH è uno pneumatico a tele incrociate specificamente sviluppato per operazioni portuali e nelle miniere sotterranee. La particolare protezione del fianco, insieme al battistrada solido, evita danni da tagli e perforazioni, piuttosto comuni in questi ambienti esigenti. Se dovete spostare carichi pesanti in condizioni dure, POWER TRAX HD SMOOTH è lo pneumatico ideale per le vostre esigenze.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Movimentatore per container • Carrello  
elevatore

OTR: Veicolo per miniere sotterranee

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
12.00 - 20	STANDARD	94007882	20	8.50	9.0	12.6	45.3	TT	E11-106R-005561
12.00 - 20	STANDARD	94062997	28	8.50	9.0	12.6	45.3	TT	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..