

POWER TRAX HD - Scheda tecnica



Description

Lo pneumatico premium POWER TRAX HD è appositamente progettato per le attrezzature in applicazioni portuali e sotterranee. Il battistrada profondo, la parete laterale extra spessa e il rivestimento resistente offrono una durata eccezionale riducendo al minimo il rischio di forature e danni accidentali. Lo pneumatico presenta un'eccellente resistenza al taglio e ai trucioli, ed è particolarmente adatto per superfici ruvide e dure. La protezione dei cerchioni, appositamente progettata, previene danni alla piana e alle ruote nell'area della flangia del cerchione.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Movimentatore per container
OTR: Veicolo per miniere sotterranee

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
12.00 - 20	IMPLEMENT	172 A8	20	8.50	9.0	320	1150	TT	E11-106R-003422
12.00 - 20	IMPLEMENT	173 A8	28	8.50	9.0	320	1150	TT	E11-106R-003348
12.00 - 20	STANDARD		20	8.50	9.0	320	1150	TT	
12.00 - 20	STANDARD		28	8.50	9.0	320	1150	TT	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..