

PRO RIB F2M - Specifiche tecniche



Description

PRO RIB F2M è un pneumatico agricoltura per trattori 2WD/2RM nelle operazioni per la lavorazione del terreno. Lo pneumatico è particolarmente idoneo per tutte le operazioni che richiedono un alto livello di manipolazione.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore 2WD
Industriale: Rimorchio

Version	STANDARD
Type	TL
Tyre Size	11L - 15 SL
LI/SS	106 A8

Dimensions US Standard

Usa code	94020461
Ply Rating	8
Section Width (inch)	11
Overall Diameter (inch)	31.3
Static Loaded Radius (inch)	14.6
Rolling Circumference (inch)	93.3
Rim Rec	8 LB
Rim Alt	10 LB
ECE	E11-106R-004588
TRA Code	F2M

Load capacity (lbs)

mph / psi	44
25	2090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 02:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..