

## PRO RIB F2M - Specifiche tecniche



### Description

PRO RIB F2M è un pneumatico agricoltura per trattori 2WD/2RM nelle operazioni per la lavorazione del terreno. Lo pneumatico è particolarmente idoneo per tutte le operazioni che richiedono un alto livello di manipolazione.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore 2WD  
Industriale: Rimorchio

Version	STANDARD
Type	TL
Tyre Size	14L - 16.1 SL
LI/SS	127 A8

## Dimensions US Standard

Usa code	94020485
Ply Rating	12
Section Width (inch)	14
Overall Diameter (inch)	38.6
Static Loaded Radius (inch)	17.8
Rolling Circumference (inch)	115
Rim Rec	W 11 C
ECE	E4-106R-002331
TRA Code	F2M

## Load capacity (lbs)

mph / psi	52
25	3860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 02:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..