

## RIB 324 - Scheda tecnica



### Description

Il RIB 324 è stato progettato con uno speciale disegno del battistrada multiblocco e un'ampia area di contatto per fornire le migliori caratteristiche di stabilità e galleggiamento su terreni morbidi e sabbiosi. La robusta carcassa e il fianco in nylon, insieme alla speciale miscela del battistrada, garantiscono un'eccellente resistenza alle forature e all'usura, nonché una maggiore capacità di carico.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Attrezzi agricoli

Industriale: Rimorchio

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	Type
66 X 44.00 - 25	STANDARD	20	36.0 TH		1110	1700	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..