

RIB 713 - Specifiche tecniche



Description

RIB 713 è uno pneumatico con cinture in acciaio per attrezzi agricoli. In risposta alla crescente consapevolezza in tema di bassa compattazione del suolo nell'agricoltura moderna, RIB 713 è stato sviluppato con la tecnologia IF. Di conseguenza, lo pneumatico è in grado di sostenere carichi più pesanti a pressioni di gonfiaggio inferiori e fornisce un'impronta più larga con distribuzione uniforme del peso. La struttura cinturata in acciaio garantisce una straordinaria resistenza alla perforazione e quindi maggiore protezione contro la penetrazione di steli e i conseguenti danni, anche in presenza di stoppie insidiose. Inoltre, la categoria velocità "D" (65 km/h – 40 mph) consente veloci trasferimenti su strada. RIB 713 è il contributo BKT per massimizzare la produttività e l'efficienza della vostra azienda agricola.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Attrezzi agricoli

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	IF 240/80 R 15
LI/SS	129 D

Dimensions International Standard

Section Width (mm)	240
Overall Diameter (mm)	765
Static Loaded Radius (mm)	354
Rolling Circumference (mm)	2324
SRI (mm)	360
Rim Rec	W 8
ECE	E11-106R-002971
TRA Code	I1

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0
From 10 to 65 km/h	540	685	835	945	1095	1240	1370	1500	1650	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..