

RIB 774 (B) - Specifiche tecniche



Description

RIB 774 (B) è uno pneumatico a sezione bassa per attrezzi agricoli, ideale per l'agricoltura moderna. Lo pneumatico è idoneo per applicazioni su strada e fuori strada con attrezzi agricoli e rimorchi. Lo pneumatico offre elevata capacità di carico e un lungo ciclo di vita del prodotto. È disponibile una versione "HD" per servizi pesanti.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio
Industriale: Rimorchio

| | |
|--------------------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 15.0/55 - 17 |
| LI/SS FREE ROLLING | 141 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 14 |
| Section Width (mm) | 391 |
| Overall Diameter (mm) | 850 |
| Static Loaded Radius (mm) | 377 |
| Rolling Circumference (mm) | 2490 |
| Rim Rec | 13.00 |
| Rim Alt | 13 |
| ECE | E11-106R-004311 |

Load capacity (Kg)

| km/h / bar | 3.70 |
|------------|------|
| 10 FR | 3605 |
| 25 FR | 3065 |
| 30 FR | 2885 |
| 40 FR | 2575 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..