

RIB 774 (C) - Specifiche tecniche



Description

RIB 774 (C) è uno pneumatico a sezione bassa con base stretta (narrow) per attrezzi agricoli, ideale per l'agricoltura moderna. Lo pneumatico è idoneo per applicazioni di raccolta del fieno e di trasporto con presse per balle di fieno e rimorchi su strada e fuori strada. Lo pneumatico offre elevata capacità di carico e un lungo ciclo di vita del prodotto.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	215/75 - 17.5
LI/SS FREE ROLLING	139 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	220
Overall Diameter (mm)	775
Static Loaded Radius (mm)	360
Rolling Circumference (mm)	2310
Rim Rec	6.75
ECE	E4-54R-0015341

Load capacity (Kg)

	km/h / bar	9.00
	10 FR	3710
	25 FR	3155
	30 FR	2970
	40 FR	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 09:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..