

RIB 900 - Scheda tecnica



Description

RIB 900 è uno pneumatico idoneo per il trasporto, la lavorazione del terreno nonché la raccolta del fieno con rimorchi, attrezzi agricoli e presse per balle di fieno. Lo pneumatico offre eccellente capacità di carico insieme ad un ciclo di vita prolungato.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Pressa per balle di fieno • Mietitrebbia •
Attrezzi agricoli • Rimorchio

SIZE	Version	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
400/60 - 15.5	STANDARD	139 A8	10	AG 13.00		405	875	380	2564	TL	
400/60 - 15.5	STANDARD	145 A8	14	AG 13.00		405	875	380	2564	TL	E4-106R-001551
400/60 - 15.5	STANDARD	147 A8	16	AG 13.00		405	875	380	2564	TL	E4-106R-001548

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..