

RIB TRAILER - Specifiche tecniche



Description

RIB TRAILER è uno pneumatico diagonale appositamente progettato per applicazioni su strada e fuoristrada con macchine utensili, in particolare mietitrici di paglia. Il suo design a 4 costole ottimizza la distribuzione del carico e la robusta carcassa garantisce resistenza alle stoppie. RIB TRAILER è stato progettato con una speciale mescola che garantisce un'ottima durata del pneumatico grazie alla sua elevata resistenza all'usura.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS	94 A6

Dimensions US Standard

Usa code	94070220
Ply Rating	8
Section Width (inch)	6.7
Overall Diameter (inch)	28.9
Rim Rec	4.50 E
Rim Alt	4.00 E ; 5 K ; 5.00 F

Load capacity (lbs)

mph / psi	68
25	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..