

RM 2002 - Specifiche tecniche



Description

RM 2002 è uno pneumatico idoneo per le operazioni di trasporto con trailer e autocarri leggeri sia sulla strada che fuoristrada. Lo pneumatico assicura lunga durabilità ed elevate performance durante l'intero ciclo di vita del prodotto. La sua versione "industrial" è ideale per gru mobili "pick & carry".

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Rimorchio
Industriale: Gru mobile

Version	INDUSTRIAL
Type	TT
Tyre Size	11.00 - 20

Dimensions International Standard

Ply Rating	18
Section Width (mm)	302
Overall Diameter (mm)	1101
Rim Rec	8.0
Rim Alt	7.5 ; 8.5

Load capacity (Kg)

	km/h / bar	8.25	7.60
100 LS		3350	-
100 LD		-	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..