

ROCK GRIP (T) - Specifiche tecniche



Description

ROCK GRIP (E-4) è ideale per camion con cassone ribaltabile nelle applicazioni per cave e di trasporti brevi nelle miniere portando carichi pesanti. La speciale miscela del battistrada riduce al minimo tagli e forature anche sui terreni più insidiosi. ROCK GRIP (E-4) offre una trazione eccezionale insieme ad un lungo ciclo di vita.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Carro con cassone ribaltabile • Dumper rigido

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	315
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	595
Rolling Circumference (mm)	3755
Rim Rec	8.5
Rim Alt	8.0

Load capacity (Kg)

km/h / bar	7.60
80 LS/LD	3750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..