

ROCK STAR IND4 - Specifiche tecniche



Description

ROCK STAR PORT IND-4 è stato particolarmente sviluppato per carrelli elevatori e macchine per la movimentazione di container vuoti. Oltre alla trazione eccellente, la miscela unica del battistrada garantisce straordinaria resistenza a tagli e lacerazioni. ROCK STAR PORT IND-4 offre un'elevata capacità di carico e un'eccellente durabilità.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Movimentatore per container vuoti • Carrello elevatore

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	14.00 - 24

Dimensions US Standard

Usa code	94063352
Ply Rating	28
Overall Width (inch)	15.4
Overall Diameter (inch)	56.1
Static Loaded Radius (inch)	25
Rolling Circumference (inch)	171.3
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

Load capacity (lbs)

mph / psi	145
5	29750

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..