

ROCK STAR (SB SPL) - Scheda tecnica



Description

ROCK STAR è stato particolarmente sviluppato per mezzi impiegati sia su strada che su rotaie in acciaio. ROCK STAR è uno pneumatico a 32 tele che offre elevata capacità di carico. La miscela unica del battistrada è particolarmente resistente a tagli e lacerazioni mentre le cinture in acciaio sono sinonimo di durabilità.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Veicolo strada-rotaia

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	Type
14.00 - 24	STEEL BELTED SPL	IND4	32	10.00 WA	10.00 VA	390	1425	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..