

RT 853 - Scheda tecnica



Description

RT 853 è uno pneumatico R-1 per trattori e vendemmiatrici per la lavorazione della terra e le operazioni di vendemmia. Lo pneumatico offre eccellente trazione, elevata capacità di carico nonché ottime proprietà di autopulitura.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Trattore • Vendemmiatrice

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
480/80 R 38 (18.4 R 38)	STANDARD	R1	149 A8/B	W 16 L	W 15 L ; W 14 L	475	1747	793	5300	825	TL	E4-106R-001822
520/85 R 38 (20.8 R 38)	STANDARD	R1	155 A8/B	DW 16 L	DW 18 L ; DD 16 L	516	1849	830	5592	875	TL	E4-106R-001483

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 03:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..