

SAND KING - Specifiche tecniche



Description

SAND KING è uno pneumatico con disegno del battistrada a blocchi particolarmente sviluppato per rimorchi nelle applicazioni di trasporto. Assicura eccellente trazione su superfici sabbiose insieme ad ottimo contatto con il terreno.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Rimorchio

Version	STANDARD
Type	TT
Tyre Size	425 / 90 D - 21 (15.00 - 21)

Dimensions US Standard

Usa code	94068814
Ply Rating	18
Section Width (inch)	16.5
Overall Diameter (inch)	52.4
Rim Rec	11.25

Load capacity (lbs)

	mph / psi	95
	40	10900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/02/2025 11:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..