

## SIERRA MAX PRO - Scheda tecnica



### Description

SIERRA MAX PRO è il pneumatico BKT perfetto per applicazioni ATV, comprese le corse side-by-side. La sua costruzione radiale e la speciale impronta a terra più ampia offrono una guida più fluida, ottimizzando la trazione laterale e anteriore. Speciali ramponi robusti sono stati appositamente studiati per fornire un'eccellente trazione e una salda aderenza al terreno. Queste caratteristiche garantiscono una guida straordinariamente confortevole, offrendo sicurezza e controllo alla guida. SIERRA MAX PRO offre prestazioni eccellenti su ogni tipo di terreno, dai terreni duri ai terreni sciolti.

### UM

US Standard

### Construction



RADIAL

### Machinery

Agricoltura: Veicolo ATV

SIZE	Version	USACode	Star R	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>AT 25 X 8 R 12</b>	STANDARD	94067077	***	43 N	6.5		7.9	24.8	11.3	73.2	TL	E11-75R-005088
<b>AT 27 X 11 R 14</b>	STANDARD	94066155	***	56 N	9.00		11.2	27.9	13.2	84.4		E11-75R-005098

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..