

SKID POWER SK - Scheda tecnica



Description

SKID POWER SK è stato particolarmente sviluppato per pale skid steer nelle applicazioni per il settore costruzioni. I cordoli di protezione del fianco e del cerchio nonché il battistrada extra profondo forniscono un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

Industriale: Pala Skid Steer

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10 - 16.5	STANDARD		10	8.25		270	775	355	2286	TL	
10 - 16.5	STANDARD		8	8.25		270	775	355	2286	TL	
10 - 16.5	STANDARD	138 A2	12	8.25		270	775	355	2286	TL	
10 - 16.5	IMPLEMENT	116 A8	8	8.25		270	775	355	2286	TL	E11-106R-003543
10 - 16.5	IMPLEMENT	120 A8	10	8.25		270	775	355	2286	TL	E11-106R-003544
12 - 16.5	IMPLEMENT	130 A8	12	9.75		312	825	375	2434	TL	E11-106R-003568
12 - 16.5	IMPLEMENT	125 A8	10	9.75		312	825	375	2434	TL	E11-106R-003545
12 - 16.5	STANDARD		10	9.75		312	825	375	2434	TL	
12 - 16.5	STANDARD		12	9.75		312	825	375	2434	TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 23:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..